



DETECTOR

GA-72CD-ML

Applications

Handheld

Technologies

Magnetometers

Last update

October 16, 2019

General description

The GA-72Cd Locator detects the magnetic field of iron and steel objects. It provides audio detection signals that peak in frequency when the locator's tip is held directly over the target. The GA-72Cd has the option of nulling or peaking.

Designed for one-hand operations, the On/Off-Sensitivity and Volume controls are located on the underside of the cover. This provides easy access, protects the knobs and contributes to their overall ruggedness and dependability.

The GA-72Cd-ML is designed specifically for military use.

Working characteristics

Analog output for data logger entry

Lightweight, easy-to-use-design reduces search time

Modular construction and high performance components

Patented HeliFlux® sensors

No response to aluminum, brass, or copper

One Year Warranty for UXO use

Radio, audio, visual, sensitivity data

Audio output	Switch at "A" Signal increases or decreases in volume with gradient-field intensity. Switch at "B" Signal increases or decreases in frequency with gradient-field intensity
Visual display	Digital readout and expanding bar graphs indicate polarity (+ or-) and relative strength of the magnetic field
Sensitive adjustment	
Connectivity	Analog output for data logger entry

Power supply data

Battery	Two rechargeable 9V NiMH batteries
Low battery alert	
Low battery alert information	4-segment LCD BATT indicator
Rechargeable	
Operating time	60 hours
Operating time information	60 Hours (intermittent use)
Battery charger provided	
Battery charger information	NiMH Battery Charger

Dimensional data

Length	880 mm
Weight	1.18 kg
Search head size	32 mm

Shape	Stick
Transport case provided	
Transport case information	Comes with Hard Case & Battery Charger
Transport case weight	0.9 kg
Transport case weight info	92 cm x 13 cm x 16 cm

Factory support data

Factory support	Our customer support department is committed to providing prompt response and 100% satisfaction. Most Schonstedt locators returned to the factory for a paid repair will be completely refurbished.
Warranty	1 Year Warranty for EOD and UXO Use
Humidity (limitations)	Operating Temperature: -13° to 140°F (-25° to 60°C)
Water resistant	
Temperature limitations	Operating Temperature: -13° to 140°F (-25° to 60°C)

Price

Base price	1299 €
Reduction for higher quantity	Call 1-888-367-7014 or email schonstedt.orders@spx.com for additional pricing.

Other

Detectors systems in use to date	GA-52Cx; GA-72Cd
Other models	GA-52Cx; GA-72Cd

GA-72CD-ML

Images

