



PPE

# SD SDV VEST

## Applications

Handheld  
Protective clothing

## Types

Metal detectors (MD)

## Last update

01/01/1970

## General description

The SDV body-armour (NATO STANAG 2920 V50 – 450m/s) is versatile enough for deminers and supervisors, providing vital area protection whether walking around or excavating anti-personnel mines. The design is simple and effective. The SDV body-armour can be worn short or long, depending on your activity at the time. Adjustment is as simple as unfastening a Velcro tab.

## Working characteristics

With a multi-layer aramid inner covered by a removable washable cover, it weighs 2.5kg complete with a polycarbonate chest insert that brings vital area protection above 450 m/s. The ventilated Cordura back does not provide protection, but does ensure that the weight rests on the shoulders and so increases comfort. A large collar interfaces with the SD full-face visor, so providing assured frontal protection in line with IMAS 10.30

## Radio, audio, visual, sensitivity data

Transmission frequency	0.00 kHz
Depth	0.00 cm

## Power supply data

Operating time	0.00 hours
----------------	------------

## Dimensional data

Length	0.00 mm
Weight	2.50 kg
Sizes available	Small, Medium, Large, X Large
Search head size	0.00 mm
Transport case weight	0.00 kg
Overall length	0.00 mm
Length with attachment	0.00 mm
Overall Width	0.00 mm
Overall Hight	0.00 mm

## Factory support data

Warranty	12 months
----------	-----------

## Price

Base price	398.00 €
------------	----------

# Other

Colours available	UN Blue, Black and Navy blue
-------------------	------------------------------

# Technical data

Maximum speed	0.00 km/h
Max trop duration (no wind)	0.00 minutes
Max hovering duration (no wind)	0.00 minutes
Max flight distance (no wind)	0.00 m
Max wind speed resistance	0.00 km/h
Operating frequency	0.00 GHz

# Operational data

Hill climbing ability (max gradient degrees)	0.00 °
Rotation speed from	0.00 rpm
Rotation speed to	0.00 rpm
Clearance depth in varying terrain from	0.00 cm
Clearance depth in varying terrain to	0.00 cm
Working speed for light soil with medium vegetation	0.00 m2/h
Working speed for medium soil with medium vegetation	0.00 m2/h
Working speed for heavy soil with dense vegetation	0.00 m2/h
Greatest remote controlled distance	0.00 m

# Engine specifications

Engine max power	0.00 hp
Engine max power at	0.00 rpm
Fuel capacity	0.00 l
Fuel consumption	0.00 l/h
Oil capacity	0.00 l

# Vehicle electrical system

Battery voltage	0.00 Volt
Battery capacity	0.00 Ah

# Protective performance

Protection level	V50 - 450 m/s
------------------	---------------

Other information

## Images

